

This Design submission has been carried out by an Authorised SAP Assessor. It has been prepared from plans and specifications and may not reflect the property as constructed.

Assessor Name Mr Martin Gill (OCDEA) **Assessor Number** 1756
Client
Date Last Modified 30/03/2009
Address 16 Willingham Way, Kingston Upon Thames, Surrey, KT1 3JA

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

1. Overall dwelling dimensions

	Area (m ²)		Average storey height (m)		Volume (m ³)
Ground Floor	38.24	(1a)	2.34	=	89.48
First Floor	38.34	(2a)	2.65	=	101.60
Total floor area (1a)+(2a)+(3a)+(4a)+(4b)+(4d)+(4f)+(4h) =	76.58	(5)			
Dwelling volume				(1)+(2)+(3)+(4)+(4c)+(4e)+(4g)+(4i) =	191.08

2. Ventilation rate

			m ³ per hour		
Number of chimneys	0	× 40 =	0	(7)	
Number of open flues	0	× 20 =	0	(8)	
Number of intermittent fans or passive vents	2	× 10 =	20	(9)	
Number of flueless gas fires	0	× 40 =	0	(9a)	
Infiltration due to chimneys, flues and fans = (7)+(8)+(9)+(9a) =			20		÷ box (6) =
<i>If a pressurisation test has been carried out, proceed to box (19)</i>					0.10
Number of storeys in the dwelling			2	(11)	
Additional infiltration					[(11) - 1] × 0.1 =
Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction					N/A
If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0					N/A
If no draught lobby, enter 0.05, else enter 0					N/A
Percentage of windows and doors draught stripped			N/A	(16)	
<i>Enter 100 in box (16) for new dwellings which are to comply with Building Regulations</i>					
Window infiltration					0.25 - [0.2 × (16) ÷ 100] =
Infiltration rate				(10)+(12)+(13)+(14)+(15)+(17) =	N/A
If based on air permeability value, then [$\frac{Q_{50}}{V}$] + (10) in box (19), otherwise (19) = (18)					0.60
<i>Air permeability value applies if a pressurisation test has been done or the design air permeability is being used</i>					

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

Number of sides on which sheltered <i>(Enter 2 in box (20) for new dwellings where location is not shown)</i>		1	(20)
Shelter factor	$1 - [0.075 \times (20)] =$	0.93	(21)
Adjusted infiltration rate	(19) \times (21) =	0.56	(22)
Calculate effective air change rate for the applicable case			
If balanced whole house mechanical ventilation system	air throughput (ach) =	N/A	(22a)
If balanced with heat recovery	efficiency in % allowing for in-use factor =	N/A	(22b)
a) If balanced whole house mechanical ventilation with heat recovery	(22) + (22a) \times [1 - (22b) / 100] =	N/A	(23)
b) If balanced whole house mechanical ventilation without heat recovery	(22) + (22a) =	N/A	(23a)
c) If whole house extract ventilation or positive input ventilation from outside <i>if (22) < 0.25, then (23b) = 0.5; otherwise (23b) = 0.25 + (22)</i>		N/A	(23b)
d) If natural ventilation or whole house positive input ventilation from loft <i>if (22) \geq 1, then (24) = (22); otherwise (24) = 0.5 + [(22)² \times 0.5]</i>		0.66	(24)
Effective air change rate - enter (23) or (23a) or (23b) or (24) in box (25)		0.66	(25)

3. Heat losses and heat loss parameter

ELEMENT	Area (m ²)	×	U - value	=	AXU (W/K)	
Windows *	11.53	×	2.44	=	28.09	(27)
Doors	1.72	×	3.90	=	6.72	(26)
Ground Floor	38.24	×	0.79	=	30.21	(28)
Walls	73.58	×	0.80	=	58.86	(29)
Roof	38.24	×	0.16	=	6.12	(30)
Total area of elements ΣA , m ²	163.31					(32)

** for windows and rooflights, use effective window U-value calculated as given in paragraph 3.2*

Fabric heat loss, W/K	(26)+(27)+(27a)+(27b)+(28)+(29)+(29a)+(30)+(30a)+(31) =	130.00	(33)
Thermal bridges - $\Sigma (l \times \Psi)$ calculated using Appendix K <i>if details of thermal bridging are not known calculate $\gamma \times$ (32) [see Appendix K] and enter in box (34)</i>		24.50	(34)
Total fabric heat loss	(33)+(34) =	154.50	(35)
Ventilation heat loss	(25) \times 0.33 \times (6) =	41.39	(36)
Heat loss coefficient, W/K	(35)+(36) =	195.89	(37)
Heat loss parameter (HLP), W/m ² K	(37) \div (5) =	2.56	(38)

4. Water heating energy requirement

kWh/year

Energy content of hot water used from Table 1 column (b)		1801.22	(39)
--	--	---------	------

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

Distribution loss from Table 1 column (c)	317.86	(40)
<i>If instantaneous water heating at point of use, enter "0" in boxes (40) to (45)</i>		
<i>For community heating use Table 1 (c) whether or not hot water tank is present</i>		
Water storage loss:		
a) If manufacturer's declared loss factor is known (kWh/day):	N/A	(41)
Temperature factor from Table 2b	N/A	(41a)
Energy lost from water storage, kWh/year	$(41) \times (41a) \times 365 =$	N/A (42)
b) If manufacturer's declared cylinder loss factor is not known:		
Cylinder volume (litres) including any solar storage within same cylinder	N/A	(43)
<i>If community heating and no tank in dwelling, enter 110 litres in box (43)</i>		
<i>Otherwise, if no stored hot water (this includes instantaneous combi boilers), enter '0' in box (43)</i>		
Hot water storage loss factor from Table 2 (kWh/litre/day)	0.00	(44)
<i>If community heating and no tank in dwelling, use cylinder loss from Table 2 for 50 mm factory insulation in box (44)</i>		
Volume factor from Table 2a	0.00	(44a)
Temperature factor from Table 2b	0.00	(44b)
Energy lost from water storage, kWh/year	$(43) \times (44) \times (44a) \times (44b) \times 365 =$	0.00 (45)
Enter (42) or (45) in box (46)	0.00	(46)
If cylinder contains dedicated solar storage, box (47) = $(46) \times [(43) - (H11)] / (43)$, else (47) = (46)	0.00	(47)
Primary circuit loss from Table 3	0.00	(48)
Combi loss from Table 3a (enter "0" if no combi boiler)	596.62	(49)
Solar DHW input calculated using Appendix H (enter "0" if no solar collector)	0.00	(50)
Output from water heater, kWh/year	$(39) + (40) + (47) + (48) + (49) - (50) =$	2715.70 (51)
Heat gains from water heating	$0.25 \times [(39) + (49)] + 0.8 \times [(40) + (47) + (48)] =$	853.75 (52)
<i>include (47) in calculation of (52) only if cylinder is in the dwelling or hot water is from community heating</i>		

	Watts	
Lights, appliances, cooking and metabolic (Table 5)	463.24	(53)
Reduction of internal gains due to low energy lighting (calculated in Appendix L)	54.16	(53a)
Additional gains from Table 5a	10.00	(53b)
Water heating	$(52) \div 8.76 =$	97.46 (54)
Total internal gains	$(53) + (53b) + (54) - (53a) =$	516.54 (55)

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

6. Solar gains

	Access factor Table 6d	×	Area m ²	×	Flux Table 6a	x 0.9 x		g Table 6b	×	FF Table 6c	=	Gains (W)	
West	0.77	×	7.67	×	48.00	x 0.9 x		0.76	×	0.70	=	135.67	(57)
East	0.77	×	3.86	×	48.00	x 0.9 x		0.76	×	0.70	=	68.36	(59)
Total solar gains:											[(56) + + (64)] =	204.03	(65)
<i>Note: for new dwellings where overshadowing is not known, the solar access factor is '0.77'</i>													
Total gains, W											(55) + (65) =	720.56	(66)
Gain/loss ratio (GLR)											(66) ÷ (37) =	3.68	(67)
Utilisation factor (Table 7, using GLR in box (67))												0.99	(68)
Useful gains, W											(66) × (68) =	715.16	(69)

7. Mean internal temperature

			°C	
Mean internal temperature of the living area (Table 8)			18.80	(70)
Temperature adjustment from Table 4e, where appropriate			0.00	(71)
Adjustment for gains <i>R is obtained from the 'responsiveness' column of Table 4a or Table 4d</i>		{[(69) ÷ (37)] - 4.0} × 0.2 × R =	-0.07	(72)
Adjusted living room temperature		(70) + (71) + (72) =	18.73	(73)
Temperature difference between zones (Table 9)			1.66	(74)
Living area fraction (0 to 1.0)		living room area ÷ (5) =	0.20	(75)
Rest-of-house fraction		1 - (75) =	0.80	(76)
Mean internal temperature		(73) - [(74) × (76)] =	17.41	(77)

8. Degree days

Temperature rise from gains	(69) ÷ (37) =	3.65	(78)
Base temperature	(77) - (78) =	13.75	(79)
Degree-days, use box (79) and Table 10		1725.97	(80)

9. Space heating requirements

Space heating requirement (useful), kWh/year	0.024 × (80) × (37) =	8114.47	(81)
--	-----------------------	---------	------

For range cooker boilers where efficiency is obtained from the Boiler Efficiency Database or manufacturer's declared value, multiply the result in box (81) by (1 - Φ_{case}/Φ_{water}) where Φ_{case} is the heat emission from the case of the range cooker at fullload (in kW); and Φ_{water} is the heat transferred to water at full load (in kW). Φ_{case} and Φ_{water} are obtained from the database record for the range cooker boiler or manufacturer's declared value.

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

9a. Energy requirements - individual heating systems, including micro-CHP

Note: when space and water heating is provided by community heating use the alternative worksheet 9b

Space heating:

Fraction of heat from secondary/supplementary system (use value from Table 11, Table 12a or Appendix F)	0.00	(82)
Efficiency of main heating system, %	78.60	(83)
<i>(SEDBUK or from Table 4a or 4b, adjusted where appropriate by the amount shown in the 'efficiency adjustment' column of Table 4c)</i>		
Efficiency of secondary/supplementary heating system, % (use value from Table 4a or Appendix E)	0.00	(84)
Space heating fuel (main) requirement, kWh/year	$[1 - (82)] \times (81) \times 100 \div (83) =$	10323.75 (85)
Space heating fuel (secondary), kWh/year	$(82) \times (81) \times 100 \div (84) =$	N/A (85a)

Water heating:

Efficiency of water heater, %	78.60	(86)
<i>(SEDBUK or from Table 4a or 4b, adjusted where appropriate by the amount shown in the 'efficiency adjustment' column of Table 4c)</i>		
Energy required for water heating, kWh/year	$(51) \times 100 \div (86) =$	3455.09 (86a)

Electricity for pumps and fans:

	kWh/year	
each central heating pump, (Table 4f)	130.00	(87a)
each boiler with a fan-assisted flue (Table 4f)	45.00	(87b)
warm air heating system fans (Table 4f)	0.00	(87c)
mechanical ventilation -balanced, extract or positive input from outside (Table 4f)	0.00	(87d)
maintaining keep-hot facility for gas combi boiler (Table 4f)	0.00	(87e)
pump for solar water heating (Table 4f)	0.00	(87f)
Total electricity for the above equipment, kWh/year	$(87a)+(87b)+(87c)+(87d)+(87e)+(87f) =$	175.00 (87)

10a. Fuel costs - individual heating systems

	Fuel kWh/year		Fuel price (Table 12)		Fuel cost £/year	
Space heating - main system	(85)	×	1.63	× 0.01 =	168.28	(88)
Space heating - secondary	(85a)	×	N/A	× 0.01 =	0.00	(89)
Water heating						
Water heating cost (electric, off-peak tariff)						
On-peak fraction (Table 13, or Appendix F for electric CPSUs)			0.00			(90)
Off-peak fraction		1.0 - (90) =	1.00			(90a)
			Fuel price			
On-peak cost	(86a) × (90)	×	N/A	× 0.01 =	0.00	(91)
Off-peak cost	(86a) × (90a)	×	N/A	× 0.01 =	0.00	(91a)
Water heating cost (other fuel)	(86a)	×	1.63	× 0.01 =	56.32	(91b)

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

Pump and fan energy cost	(87)	×	7.12	×	0.01 =	12.46	(92)
Energy for lighting (calculated in Appendix L)	361.09	×	7.12	×	0.01 =	25.71	(93)
Additional standing charges (Table 12)						34.00	(94)
Renewable and energy-saving technologies (Appendices M and N)							
PV							
Energy produced or saved, kWh/year	2743.06	(95)					
Cost of energy produced or saved, £/year	(95)	×	6.41	×	0.01 =	175.83	(95a)
Wind							
Energy produced or saved, kWh/year	0.00	(95b1)					
Cost of energy produced or saved, £/year	(95b1)	×	0.00	×	0.01 =	N/A	(95b)
Micro CHP							
Energy produced or saved, kWh/year	N/A	(95c1)					
Cost of energy produced or saved, £/year	(95c1)	×	N/A	×	0.01 =	N/A	(95c)
Energy consumed by the technology, kWh/year	N/A	(96)					
Cost of energy consumed, £/year	(96)	×	N/A	×	0.01 =	N/A	(96a)
Special features (Appendix Q)							
Energy produced or saved, kWh/year	N/A	(s1)					
Cost of energy produced or saved, £/year	(s1)	×	N/A	×	0.01 =	N/A	(s1a)
Energy consumed by the technology, kWh/year	N/A	(s2)					
Cost of energy consumed, £/year	(s2)	×	N/A	×	0.01 =	N/A	(s2a)
Total energy cost	(88)+(89)+(91)+(91a)+(91b)+(92)+(93)+(94)-(95a)-(95b)-(95c)+(96a)-(s1a)+(s2a) =					120.94	(97)

11a. SAP rating - individual heating systems

Energy cost deflator (SAP 2005)						0.91	(98)
Energy cost factor (ECF)	[[(97) × (98)] - 30.0] ÷ [(5) + 45.0] =					0.66	(99)
SAP rating (Table 14)						91	(100)
SAP band						B	

12a. Carbon dioxide emissions rate for individual heating systems (including micro-CHP) and community heating without CHP

Individual heating system:	Energy kWh/year		Emission factor kg CO ₂ /kWh		Emissions kgCO ₂ /year		
Space heating main from box (85)	10323.75	×	0.194	=	2002.81	(101)	
Space heating secondary from box (85a)	N/A	×	N/A	=	0.00	(102)	
Energy for water heating from box (86a)	3455.09	×	0.194	=	670.29	(103)	
Energy for water heating (51) or [(87b*) × 100 ÷ (104)] =	N/A	×	N/A	=	N/A	(106)	
Space and water heating	[(101) + (102) + (103)] or [(105) + (106)] =					2673.09	(107)

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

Energy for water heating	(Type 1 fraction) × (87*) × 100 ÷ (104a)	=	<input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>	=	<input type="text" value="N/A"/>	(106a)
Energy for water heating	(Type 2 fraction) × (87*) × 100 ÷ (104b)	=	<input type="text" value="N/A"/>	×	<input type="text" value="0.000"/>	=	<input type="text" value="N/A"/>	(106b)
Space and water heating			[(105a) + (106a) + (105b) + (106b)] =				<input type="text" value="2673.09"/>	(107)
Electricity for pumps and fans from box (87) or (88*)			<input type="text" value="175.00"/>	×	<input type="text" value="0.422"/>	=	<input type="text" value="73.85"/>	(108)
Energy for lighting from Appendix L			<input type="text" value="361.09"/>	×	<input type="text" value="0.422"/>	=	<input type="text" value="152.38"/>	(109)
Energy produced or saved in dwelling (Appendices M and N)								
PV energy produced or saved	(95) or (95*)	×	<input type="text" value="0.57"/>	=	<input type="text" value="1558.06"/>	(110)		
Wind energy produced or saved	(95b1) or (95b1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="N/A"/>	(110b)		
Micro-CHP energy produced or saved	(95c1) or (95c1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="N/A"/>	(110c)		
Micro-CHP energy consumed	(96) or (96*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>	(111)		
Energy produced or saved in dwelling (Appendix Q)	(s1) or (s1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>	(s1a)		
Energy consumed by the technology (Appendix Q)	(s2) or (s2*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>	(s2a)		
Total CO ₂ kg/year	(107) + (108) + (109) - (110) + (111) - (s1a) + (s2a)	=				<input type="text" value="1341.27"/>	(112)	
Carbon dioxide emissions rate			(112) ÷ (5)			<input type="text" value="17.51"/>	(113)	
EI rating						<input type="text" value="85"/>		
EI band						<input type="text" value="B"/>		

13a. Primary energy, for individual heating systems (including micro-CHP) and community heating without CHP

Individual heating system:	Energy kWh/year	Primary energy factor	Primary energy (kWh/year)
Space heating main from box (85)	<input type="text" value="10323.75"/>	×	<input type="text" value="1.150"/>
Space heating secondary from box (85a)	<input type="text" value="N/A"/>	×	<input type="text" value="0.00"/>
Energy for water heating from box (86a)	<input type="text" value="3455.09"/>	×	<input type="text" value="1.150"/>
Energy for water heating	(87b*) × 100 ÷ (104) = <input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>
Space and water heating			<input type="text" value="15845.66"/>
Energy for water heating	(Type 1 fraction) × (87*) × 100 ÷ (104a) = <input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>
Energy for water heating	(Type 2 fraction) × (87*) × 100 ÷ (104b) = <input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>
Space and water heating			<input type="text" value="15845.66"/>
Electricity for pumps and fans from box (87) or (88*)	<input type="text" value="175.00"/>	×	<input type="text" value="2.800"/>
Energy for lighting from Appendix L	<input type="text" value="361.09"/>	×	<input type="text" value="2.800"/>
Energy produced or saved in dwelling (Appendices M and N)			
PV energy produced or saved	(95) or (95*)	×	<input type="text" value="2.80"/>

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control

Wind energy produced or saved	(95b1) or (95b1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="N/A"/>
Micro-CHP energy produced or saved	(95c1) or (95c1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="N/A"/>
Micro-CHP energy consumed	(96) or (96*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>
Energy produced or saved in dwelling (Appendix Q)	(s1) or (s1*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>
Energy consumed by the above technology (Appendix Q)	(s2) or (s2*)	×	<input type="text" value="N/A"/>	=	<input type="text" value="0.00"/>
Primary energy kWh/year					<input type="text" value="9666.17"/>
Primary energy kWh/m²/year					<input type="text" value="126.22"/>
Space heating from CHP or recovered/geothermal heat, box (86*)	<input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>	box (107*) =	<input type="text" value="N/A"/>
Space heating from boilers (87*) × 100 ÷ (109*) =	<input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>	Table 12 =	<input type="text" value="-1.00"/>
Electricity for pumps and fans, box (88*)	<input type="text" value="N/A"/>	×	<input type="text" value="N/A"/>	Table 12 =	<input type="text" value="N/A"/>
Total PE associated with boilers, CHP or recovered/geothermal heat <i>If negative, enter "0" in box (115*)</i>				$[(108*) + (110*) + \dots + (114*)] =$	<input type="text" value="-1.00"/>
Energy for lighting from Appendix L	<input type="text" value="361.09"/>	×	<input type="text" value="2.80"/>	Table 12 =	<input type="text" value="1011.06"/>
Energy produced or saved in dwelling (Appendix M)					
PV energy produced or saved (95*)		×	<input type="text" value="2.80"/>	Table 12 =	<input type="text" value="7680.56"/>
Wind energy produced or saved (95b1*)		×	<input type="text" value="N/A"/>	Table 12 =	<input type="text" value="N/A"/>

This draft SAP Worksheet report is for internal purposes only and should not be accepted as evidence of compliance by Building Control